

SPECIFICATION

1. Scope

This specification covers the SONOPRO transducer for cleaning under the atmosphere of $25\pm 3^{\circ}\text{C}$ 40 ~ 70%RH.

2. Type

Trans-C685052

Trans-C	68	50	52
Transducer	Frequency	Ceramic dia.	Emitting dia.

3. Dimensions

As per the drawing : Height = 65mm/m Emitting Diameter = 52mm/m

4. Electronical Specification (By Piece)

- a. Resonant Frequency $F_r = 68\text{kHz}\pm 0.5\text{kHz}$
- b. Resonant Resistance $Z_r < 20\Omega$
- c. Capacitance $\text{CAPA} = 5.75\pm 20\% \text{ nF}$
- d. $\text{tgD} (\% \text{ KHz}) < 0.5$
- e. $Q_m > 500$



5. Mechanical Characteristics (Periodical in Laboratory)

- a. Acoustic Power = $4.7\pm 0.5 \text{ Wcm}^{-2}$ -- By Ohmico Ultrasonic Power Meter UMP- DT-1AV
- b. Amplitude $> 12\mu\text{m}$ -- Peak-to-peak in sinusoidal

6. Frequency category :

- | | |
|--------------------|--------------------|
| A : 67.50~67.79kHz | B : 67.80~68.04kHz |
| C : 68.05~68.29kHz | D : 68.30~68.50kHz |

7. Impedance VS Frequency curve of Trans-C685052

